





Bobbin Thread Winder



Safety Sensor



Laser Position Marker




Sock Frame



One Print Frame



Shoe Clamp Frame





Preparatory Table



Side Clamp Frame

SPECIFICATIONS

MODEL	Head	Needles	Embroidery Area (DXW)		Maximum Speed (f.p.m.)	Stitch Length	Memory	Dimensions						
			Maximum	Low-profile Cap frame				L	W	H	A	B	C	
HCD3-1501-40	1	15	400x520mm 15.7x20.5inch	80x360mm 3.2x14.2inch	1,200	0.1-12.7mm	40,000,000 stitches 999 patterns	845	814	871	762	586	743	
								33.3	32.0	34.3	30.0	23.1	29.3	



Embroidery area may be limited by hoops to be used. ● Specifications are subject to change without notice. ● Maximum speed may change by sewing conditions.

Distributed by :

HappyJapan
Japan Inc.

OFFICE 2-9-5, Taifu, Taifu-ku, Tokyo, Japan
81-3-3834-0718 fax+81-3-3835-8917
mb-info@happyjpn.com
www.happyjpn.com

Equipment Pour l'impression Et la Création (E.P.I.C.)

11, rue Gaston Israel, 95880 Enghien-les-Bains

Email: epic.jbe@orange.fr

Tél. : +33 6 37.69.83.71

Site web : broder-avec-happy.com

HappyJapan

HappyJapan Inc.

MODEL : HCD3-1501-40